



## BRILLIANCE FLOOR FINISH

This metal-crosslinked, modified acrylic floor finish provides excellent lay down gloss and superior response to high speed burnishing. BRILLIANCE can be maintained with either conventional low-speed programs or infrequent (2-3 times a week) high speed burnishing.

**DIRECTIONS** (New or existing floors): Thoroughly strip floor with a floor finish remover. Rinse thoroughly with clean water. Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss. Apply 2-4 coats of floor finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

**MAINTENANCE:** Sweep as necessary. Damp mop or scrub lightly with a mild, neutral detergent. Spray buff or buff lightly with appropriate pad. Also excellent for high speed buffing. In high traffic areas, re-coat worn spots as necessary.

Keep out of reach of children. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to M.S.D.S. for additional safety information.


### TYPICAL PROPERTIES:

|  |                |
|--|----------------|
| Specific Gravity:.....                     | 1.04           |
| Total Solids:.....                         | 22%            |
| pH:.....                                   | 8.5            |
| James Static Coefficient of Friction:..... | 0.6            |
| Leveling:.....                             | Excellent      |
| Film Formation:.....                       | Excellent      |
| Gloss:.....                                | Excellent      |
| Water Resistance:.....                     | Excellent      |
| Detergent Resistance:.....                 | Excellent      |
| Removability:.....                         | Excellent      |
| Black Heal Mark Resistance:.....           | Excellent      |
| Appearance:.....                           | White Emulsion |
| Fragrance:.....                            | Mild Acrylic   |

Manufactured by:  
ABC COMPOUNDING COMPANY, INC.  
ATLANTA, GA / DALLAS, TX



LX0109/1106



### FEATURES

Modified Hard Acrylic  
Polymers

Superior Gloss  
Durability, Leveling

Outstanding Burnish  
Response, No  
Powdering or Dusting

UL Listed (Slip Resistance)

### BENEFITS

Decreased labor cost  
through less frequent need  
to buff, burnish and recoat,  
and a reduction in the  
number of floor strippings

### WHERE TO SELL

Hospitals / Healthcare

School Systems

Grocery / Convenience  
Stores

Shopping Centers / Malls

Sports Facilities

Office Buildings

Airports

[www.lynxclean.com](http://www.lynxclean.com)

Lynx is a Registered Trademark of  
ABC Compounding Co., Inc.