



# Safety Data Sheet

## LYNX GRAFFITI REMOVER II

### SECTION 1: Identification

**Trade Name:** LYNX GRAFFITI REMOVER II

**Date Prepared:** 02/22/2022

**Product Identification:**4036

**Additional ID:** LX-2155

**Synonyms:** Blend of Petroleum Distillates

**Product Use Description:** Graffiti remover

**Manufactured By:**

ABC COMPOUNDING CO., INC.  
PO BOX 80729  
Conyers, GA 30013 US

**Phone:** (800) 795-9222

**Website:**www.lynxclean.com

**24 HR Emergency Number:** (800) 535-5053

### SECTION 2: Hazards Identification

#### Classifications

Aspiration Hazard - Category 1

Toxic to Reproduction - Category 2

Skin Irritation - Category 2

Skin Sensitization - Category 1

Eye Irritation - Category 2

Specific Target Organ Toxicity (repeated exposure) - Category 2

Specific Target Organ Toxicity (single exposure) - Category 1

Acute Toxicity - Inhalation - Category 4

Acute Toxicity - Oral - Category 4

Acute Toxicity - Dermal - Category 4

Flammable Aerosols - Category 1

Gasses under pressure - Liquefied gas



Flammable

Compressed Gas

Irritant

Health Hazard

**Signal Word:** Danger

#### Hazard Statements

Keep out of reach of children.

Read label and SDS before use.

Harmful if swallowed or inhaled.

Harmful in contact with skin

May be fatal if swallowed and enters airways.

Causes damage to optic nerve and central nervous system. May cause blindness.

May cause damage to central nervous system through prolonged or repeated exposure.

Suspected of damaging the unborn child via inhalation.

# Safety Data Sheet

## LYNX GRAFFITI REMOVER II

Causes skin irritation  
May cause an allergic skin reaction  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.

### Precautionary Statements

#### Prevention

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Do not breathe mist/vapors/spray.  
Use only outdoors or in a well-ventilated area.  
Keep away from heat, sparks, open flames and hot surfaces. -No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Wash hands and face thoroughly after handling.  
Wear protective gloves and clothing.  
Wear eye protection.  
Do not eat, drink or smoke when using this product.  
Contaminated work clothing must not be allowed out of the workplace.

#### Response

IF SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting.  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: get medical attention  
Take off contaminated clothing and wash before reuse.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
If eye irritation persists: Get medical attention.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a poison center or doctor if you feel unwell.  
If exposed or concerned: Get medical attention.  
Call a poison center or a doctor.

#### Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Store in a well-ventilated place.  
Store locked up.

#### Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

#### Hazards Not Otherwise Specified

Not applicable

## SECTION 3: Composition

Chemical Name	CAS #	Concentration % by Weight
Methanol	67-56-1	5 - 10
Propane	74-98-6	5 - 10
Acetone	67-64-1	30 - 40
Toluene	108-88-3	20 - 30
Diethylene Glycol Butyl Ether	112-34-5	10 - 20
N-BUTANE	106-97-8	1 - 5
D-limonene	5989-27-5	1 - 5

## SECTION 4: First Aid Measures

# Safety Data Sheet

## LYNX GRAFFITI REMOVER II

### EMERGENCY OVERVIEW

**DANGER.** Extremely flammable. Contents under pressure. Harmful or fatal if swallowed. Aspiration hazard if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

**EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**SKIN:** Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention. Take off contaminated clothing and wash it before reuse.

**INHALATION:** Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

**INGESTION:** Harmful or fatal if swallowed. Seek medical attention immediately. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

### SECTION 5: Firefighting Measures

#### **Suitable fire extinguishing media:**

Use water spray, fog or foam.

#### **Specific hazards arising from the chemical:**

Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

#### **Hazardous thermal decomposition products:**

Carbon Dioxide, Carbon Monoxide

#### **Specific fire-fighting methods:**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

#### **Special protective equipment for fire fighters:**

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

### SECTION 6: Accidental Release Measures

#### **Personal precautions:**

Put on appropriate personal protective equipment (see section 8)

#### **Environmental precautions and clean-up methods:**

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

### SECTION 7: Handling and Storage

# Safety Data Sheet

## LYNX GRAFFITI REMOVER II

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

### SECTION 8: Exposure Controls/Personal Protection

#### N-BUTANE(106-97-8)

ACGIH TLV	1000 ppm
-----------	----------

#### Toluene(108-88-3)

OSHA PEL	200 ppm
ACGIH TLV	20 ppm

#### Diethylene Glycol Butyl Ether(112-34-5)

OSHA PEL	35 ppm
ACGIH TLV	35 ppm

#### D-limonene(5989-27-5)

ACGIH TLV	8 hr TWA	30 ppm AIHA Standard
-----------	----------	----------------------

#### Methanol(67-56-1)

OSHA PEL	200 ppm
ACGIH TLV	200 ppm

#### Acetone(67-64-1)

OSHA PEL	750 ppm
ACGIH TLV	500 ppm

#### Propane(74-98-6)

ACGIH TLV	1000 ppm
-----------	----------

**Eye Protection:** Wear safety glasses or goggles.

**Skin Protection:** To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

**Respiratory Protection:** When respiratory protection is required use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

**Engineering Controls:** Good general ventilation required.

### SECTION 9: Physical and Chemical Properties

Property	Value	Property	Value
Appearance	CLEAR SPRAY/MIST	Auto Ignition Temp	NOT AVAILABLE
Boiling Point	NOT AVAILABLE	Color	COLORLESS
Decomposition Temperature	NOT AVAILABLE	Evaporation Rate	NOT AVAILABLE
Explosive Limit Ranges	NOT AVAILABLE	Explosive Properties	NOT AVAILABLE
Flash Point	< 0 F (liquid portion)	Melting/Freezing Point	NOT AVAILABLE
Odor	SOLVENT	Odor Threshold	NOT AVAILABLE
Other Information	VOC content (wt. %): <50	Oxidizing Properties	NOT AVAILABLE
Partition Coeff	NOT AVAILABLE	Physical State	LIQUID
Relative Density	0.8	Solubility (Water)	INSOLUBLE
Vapor Density	NOT AVAILABLE	Vapor Pressure	NOT AVAILABLE
Viscosity	NOT AVAILABLE	pH	NOT APPLICABLE

### SECTION 10: Stability and Reactivity

# Safety Data Sheet

## LYNX GRAFFITI REMOVER II

### Reactivity

Under normal conditions of storage and use, hazardous reactions will not occur.

### Chemical Stability

Stable under normal conditions.

### Incompatible Materials

Acids and strong oxidizers

### Conditions to Avoid

High temperatures, open flames, sparks, welding.

### Hazardous Decomposition Products

CO, CO<sub>2</sub>

Vapors may ignite at temperatures exceeding flash point.

## SECTION 11: Toxicological Information

**Primary Route of Entry:** Skin contact, inhalation

### Acute/Potential Health Effects:

**EYES:** May cause serious eye irritation. Symptoms include stinging, tearing and redness.

**SKIN:** May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns.

**INHALATION:** High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.

**INGESTION:** Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

**Chronic / Long Term Effects:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

**Target Organ Effects:** Central nervous system.

**Reproductive/Developmental Information:** Prolonged and repeated exposure of pregnant animals to Toluene (>1500 ppm) has been reported to cause adverse fetal developmental effects.

**WARNING:** This product can expose you to chemicals including Toluene and Methanol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**Carcinogenic Information:** This material is not listed as a carcinogen by IARC, NTP or OSHA.

### Acute Toxicity Values:

Toluene: Inhalation - LC50, 4 hr, rat 28.1 mg/l

Acetone: Dermal, guinea pig: LD50 = >9400 uL/kg; Draize test, rabbit, eye: 20 mg/242 Hr Moderate; Draize test, rabbit, skin: 500 mg/24 Hr Mild; Inhalation, mouse: LC50 = 44gm/m<sup>3</sup>/4H; Oral, mouse: LD50 = 3 g/kg.

Methanol: Inhalation - LC50, rat 64000 ppm; Oral - LD50, rat 5.6-13 g/Kg; Dermal - LD50, rabbit 20 ml/Kg.

## SECTION 12: Ecological Information

Toluene: LC50, Ceriodaphnia dubia, 48 hr, semistatic, 3.78 mg/l

Acetone: LC50 Fish: Rainbow trout -5540 mg/l, 96 hr; LC50 fish: Bluegill/sunfish -8300 mg/l, 95 hr.

## SECTION 13: Disposal Considerations

**Trade Name:** LYNX GRAFFITI REMOVER II  
**SDS ID:** SDS10427

**Product ID:** 403620LL  
**Revision #:** 1

**Page 5 of 7**  
**Revision Date:** 02/22/2022

# Safety Data Sheet

## LYNX GRAFFITI REMOVER II

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

### SECTION 14: Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

**UN number** 1950  
**Proper shipping name** Aerosols, flammable  
**Class** 2.1  
**Packing group** -

### SECTION 15: Regulatory Information

#### California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act)

Methanol

Toluene

#### CERCLA RQ (40 CFR 302)

Acetone 5000 LB

Methanol 5000 LB

Toluene 1000 LB

#### Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65)

Diethylene Glycol Butyl Ether

Methanol

Toluene

If identified components of this product are **CERCLA** hazardous substances and/or listed under **Sections 302, 304, or 313 of Title III** of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under **California Proposition 65** (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

#### **Title III Section 311/312** Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire (X) Pressure (X) Reactive ( ) Not Applicable ( )

**T.S.C.A. Status:** All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

**RCRA Status:** Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

D001

### SECTION 16: Other Information

#### HMIS Ratings :

<b>HEALTH</b>	3
<b>FLAMMABILITY</b>	4
<b>REACTIVITY</b>	0
<b>PERSONAL PROTECTION</b>	G

# Safety Data Sheet

## *LYNX GRAFFITI REMOVER II*

---

Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 02/22/2022

**Trade Name:** LYNX GRAFFITI REMOVER II  
**SDS ID:** SDS10427

**Product ID:** 403620LL  
**Revision #:** 1

Page 7 of 7  
**Revision Date:** 02/22/2022