

Date Prepared:

12/12/2017

SECTION 1: Identification

Trade Name: 0109 LYNX BRILLIANCE FLOOR FINISH

Product Identification: 6567

Synonyms: Polymer emulsion

Product Use Description: Floor finish

Manufactured By: ABC COMPOUNDING CO., INC. PO BOX 80729 Conyers, GA 30013 US

Phone: (800) 795-9222 Website: www.lynxclean.com

24 HR Emergency Number: (800) 535-5053

SECTION 2: Hazards Identification

Classifications

This material is not considered hazardous by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

SECTION 3: Composition

Chemical Name	CAS #	Concentration % by Weight	
Diethylene Glycol Ethyl Ether	111-90-0	1 - 5	
SECTION 4: First Aid Measures			

EMERGENCY OVERVIEW

CAUTION. May be harmful if swallowed. May irritate eyes and skin.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If

eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION: May be harmful if swallowed. Seek medical attention immediately.

SECTION 5: Firefighting Measures

Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

Containers may build pressure and rupture.

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

SECTION 6: Accidental Release Measures

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

SECTION 7: Handling and Storage

Do not use or store near heat, sparks or open flame. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Keep out of reach of children.

SECTION 8: Exposure Controls/Personal Protection

Diethylene Glycol Ethyl Ether(111-90-0)	
OSHA PEL	25 ppm
ACGIH TLV	25 ppm

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: No special requirements are needed for this material.

Engineering Controls: Good general ventilation required.

SECTION 9: Physical and Chemical Properties

Property	Value	Property	Value
Appearance	EMULSION	Auto Ignition Temp	NOT AVAILABLE
Boiling Point	NOT AVAILABLE	Color	WHITE
Decomposition Temperature	NOT AVAILABLE	Evaporation Rate	NOT AVAILABLE
Explosive Limit Ranges	NOT AVAILABLE	Explosive Properties	NOT AVAILABLE
Flash Point	NONE	Melting/Freezing Point	NOT AVAILABLE
Odor	CHARACTERISTIC	Odor Threshold	NOT AVAILABLE
Other Information	VOC content (wt. %): 0	Oxidizing Properties	NOT AVAILABLE
Partition Coeff	NOT AVAILABLE	Physical State	LIQUID
Relative Density	1.04	Solubility (Water)	COMPLETE
Vapor Density	NOT AVAILABLE	Vapor Pressure	NOT AVAILABLE
Viscosity	NOT AVAILABLE	рН	8-9

SECTION 10: Stability and Reactivity

Reactivity

Under normal conditions of storage and use, hazardous reactions will not occur. Chemical Stability Stable under normal conditions. Incompatible Materials Acids and strong oxidizers Conditions to Avoid High temperatures Hazardous Decomposition Products CO, CO2

SECTION 11: Toxicological Information

Primary Route of Entry: Skin contact

Acute/Potential Health Effects:

EYES: May cause eye irritation. Symptoms include stinging, tearing and redness.

SKIN: May cause skin irritation.

INHALATION: High vapor concentrations may be irritating to respiratory tract.

INGESTION: May cause headache, dizziness, incoordination, nausea, vomiting, diarrhea and general weakness.

Chronic / Long Term Effects: None known.

Target Organ Effects: None known.

Reproductive/Developmental Information: No data.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Acute Toxicity Values:

Not available.

SECTION 12: Ecological Information

Not available

SECTION 13: Disposal Considerations

Trade Name: 0109 LYNX BRILLIANCE FLOOR FINISH SDS ID: SDS05002

Product ID: 656705PL Revision #: 2

Page 3 of 4 Revision Date: 12/12/2017

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

SECTION 14: Transport Information

Not regulated

SECTION 15: Regulatory Information

Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65) Diethylene Glycol Ethyl Ether

If identified components of this product are CERCLA hazardous substances and/or listed under Sections 302, 304, or 313 of

<u>Title III</u> of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic () Fire () Pressure () Reactive () Not Applicable ()

T.S.C.A. Status: All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

<u>RCRA Status</u>: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

None

SECTION 16: Other Information

HMIS Ratings :



Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 12/12/2017