

Safety Data Sheet

1202 LYNX FOAMING TILE & GROUT CLEANER

Date Prepared:

Additional ID:

01/10/2018

LX-1202

SECTION 1: Identification

Trade Name: 1202 LYNX FOAMING TILE & GROUT CLEANER

Product Identification: 6067

Synonyms: Acid cleaner

Product Use Description: Tub/Tile Cleaner Manufactured By:

ABC COMPOUNDING CO., INC. PO BOX 80729 Conyers, GA 30013 US

Phone: (800) 795-9222 Website: www.lynxclean.com

24 HR Emergency Number: (800) 535-5053

SECTION 2: Hazards Identification

Classifications

Skin corrosion - Category 1 Eye Damage - Category 1 Corrosive to Metals



Signal Word: Danger

Hazard Statements

Keep out of reach of children. Read label and SDS before use. Causes severe skin burns and eye damage May be corrosive to metals

Precautionary Statements

Prevention

Do not breathe mists.

Wash hands thoroughly after handling.

Wear protective gloves and clothing.

Wear eye and face protection.

Keep only in original container.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water/shower.

Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center or a physician.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Product ID: 606732FL Revision #: 1 Immediately call a poison center or a physician. Absorb spillage to prevent material damage.

Absorb sp Storage

Store locked up.

Store in corrosive resistant plastic container.

Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

Hazards Not Otherwise Specified

Not applicable

SECTION 3: Composition

	Concentration % by	
Chemical Name	CAS #	Weight
Phosphoric Acid	7664-38-2	10 - 15
2-butoxyethanol	111-76-2	1 - 5
Hydroxyacetic Acid	79-14-1	1 - 5

SECTION 4: First Aid Measures

EMERGENCY OVERVIEW

DANGER. May be harmful if swallowed. Causes severe skin burns and eye damage. May cause respiratory irritation.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Immediately call a poison center or a physician.

SKIN: Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water/shower.

If skin irritation persists get medical attention.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or a doctor.

INGESTION: Rinse mouth. Do not induce vomiting. Seek medical attention immediately.

SECTION 5: Firefighting Measures

Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

Containers may build pressure and rupture.

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

SECTION 6: Accidental Release Measures

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Disperse vapors with water

spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb

unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

SECTION 7: Handling and Storage

Do not use or store near heat, sparks or open flame. Store in a cool, dry place. Do not get in eyes, on skin or on clothing.

Avoid breathing sprays. Keep out of reach of children.

SECTION 8: Exposure Controls/Personal Protection						
2-butoxyethanol(111-76-2)						
OSHA PEL	25 ppm (skin)					
ACGIH TLV	20 ppm					
Phosphoric Acid(7664-38-2)						
OSHA PEL	1 mg/m3					
ACGIH TLV	1 mg/m3					

Eye Protection: Wear safety glasses or goggles.

Skin Protection: Wear impervious gloves (made from rubber, nitrile or neoprene), clothing, and boots.

Respiratory Protection: When respiratory protection is required, use an organic vapor & particulate cartridge. All respiratory

programs must meet OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements.

Engineering Controls: Good general ventilation required.

SECTION 9: Physical and Chemical Properties

Property	Value	Property	Value			
Appearance	CLEAR LIQUID	Auto Ignition Temp	NOT AVAILABLE			
Boiling Point	NOT AVAILABLE	Color	PURPLE			
Decomposition Temperature	NOT AVAILABLE	Evaporation Rate	NOT AVAILABLE			
Explosive Limit Ranges	NOT AVAILABLE	Explosive Properties	NOT AVAILABLE			
Flash Point	NONE	Melting/Freezing Point	NOT AVAILABLE			
Odor	MINT	Odor Threshold	NOT AVAILABLE			
Other Information	VOC content (wt. %): 5.0	Oxidizing Properties	NOT AVAILABLE			
Partition Coeff	NOT AVAILABLE	Physical State	LIQUID			
Relative Density	1.1	Solubility (Water)	COMPLETE			
Vapor Density	NOT AVAILABLE	Vapor Pressure	NOT AVAILABLE			
Viscosity	> 100 cps	рН	< 1			
SECTION 10: Stability	and Reactivity					

SECTION 10: Stability and Reactivity

Reactivity

Under normal conditions of storage and use, hazardous reactions will not occur.

Chemical Stability Stable under normal conditions. Incompatible Materials Strong alkalis, oxidizers, organic matter, certain metals. Conditions to Avoid

High temperatures

Hazardous Decomposition Products

CO, CO2, H2

Safety Data Sheet 1202 LYNX FOAMING TILE & GROUT CLEANER

SECTION 11: Toxicological Information

Primary Route of Entry: Skin contact, eye contact, inhalation

Acute/Potential Health Effects:

EYES: Causes severe irritation experienced as discomfort or pain, excess blinking and tear production, with redness and swelling of the conjunctiva.

SKIN: Brief contact may cause slight irritation. Prolonged contact may cause more severe irritation with pain, local redness and swelling and possible tissue destruction.

INHALATION: High vapor concentrations may be irritating to respiratory tract.

INGESTION: May be harmful or fatal if swallowed. Corrosive. Can cause severe burns and complete tissue perforation of mucous membranes, mouth, throat and stomach.

Chronic / Long Term Effects: Repeated exposure may cause damage to the tissues of the mucous membranes, upper

respiratory tract, eyes and skin. 2-Butoxyethanol has caused red blood cell hemolysis in lab animals and secondary injury to the liver and kidney.

Target Organ Effects: Liver, kidney, lungs and upper respiratory tract, gastrointestinal tract, eyes, skin.

Reproductive/Developmental Information: No data.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Acute Toxicity Values:

Phosphoric Acid: Oral, rat LD50: 1530 mg/kg.

2-butoxyethanol: Ingestion - LD50, rat, 1300 mg/Kg; Dermal LD50, guinea pig 1400 mg/Kg; Inhalation - LC50, 1 hr, vapor,

guinea pig > 3.1 mg/l.

SECTION 12: Ecological Information

2-butoxyethanol: EC50, Daphnia magna, static test, 48 h, immobilization: 1550 mg/l

SECTION 13: Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

SECTION 14: Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may

not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 3264

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (CONTAINS PHOSPHORIC ACID) Proper shipping name

Class

8 Packing group Ш

SECTION 15: Regulatory Information

CERCLA RQ (40 CFR 302) Phosphoric Acid

5000 lbs

Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65) 2-butoxyethanol

Safety Data Sheet 1202 LYNX FOAMING TILE & GROUT CLEANER

If identified components of this product are **CERCLA** hazardous substances and/or listed under <u>Sections 302, 304, or 313 of</u> <u>Title III</u> of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire () Pressure () Reactive () Not Applicable ()

T.S.C.A. Status: All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

<u>RCRA Status</u>: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes

hazardous waste it would be assigned RCRA Code(s)

D002

SECTION 16: Other Information

HMIS Ratings :

HEALTH	3
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	D

Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.