



FLOOR FINISH

LYNX FLOOR FINISH is a metal cross linked, modified acrylic floor finish.

DIRECTIONS: 1) Thoroughly strip floor with a Lynx Floor Finish Remover. **2)** Rinse floor thoroughly with clean water. **3)** Apply 2-4 thin

uniform coats of floor finish allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather. **Maintenance:** Sweep as necessary. Damp mop or scrub lightly with a mild, neutral detergent. Spray buff or buff lightly with appropriate pad. Also excellent for high-speed buffing. In high traffic areas, re-coat worn spots as necessary.

CAUTION: Keep out of reach of children. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to M.S.D.S. for additional safety information.

TYPICAL PROPERTIES:

Specific Gravity:	1.02
Solids:	18%
pH:	8.3
James Static Coefficient of Friction:	0.6
Leveling:	Excellent
Film Formation:	Excellent
Gloss:	Excellent
Water resistance:	Excellent
Removability:	Excellent
Detergent resistance:	Very Good-Excellent
Black heal mark resistance:	Very Good
Odor:	Slight Ammonia
Appearance:	White emulsion



FEATURES

Excellent Gloss Good Durability

BENEFITS

Superior Response To High Speed Burnishing

Maintain With Conventional Low-speed Programs Or Infrequent (2-3 Times Per Week) High Speed Burnishing

WHERE TO SELL

Hospitals / Healthcare

School Systems

Grocery / Convenience Stores

Shopping Centers / Malls

Sports Facilities

Office Buildings

Airports

Manufactured by: ABC COMPOUNDING COMPANY, INC. ATLANTA, GA / DALLAS, TX www.lynxclean.com

Lynx is a Registered Trademark of ABC Compounding Co., Inc.

LX0101/0605