



PREMIUM FLOOR FINISH

LYNX PREMIUM FLOOR FINISH is formulated with modified acrylic polymers for both low maintenance and high speed burnishing.

DIRECTIONS:

- 1) Thoroughly strip floor with a Lynx Floor Finish Remover.
- 2) Rinse floor thoroughly with clean water.
- 3) Apply 2-4 thin uniform coats of floor finish allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

Maintenance: Dust mop, sweep or damp mop as needed. If desired, burnish with electrical, battery or propane high-speed buffers using a synthetic or synthetic / natural blend pad. Depending on traffic, burnish 1-3 times a week.


CAUTION: Keep out of reach of children. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to M.S.D.S. for additional safety information.

TYPICAL PROPERTIES:

Specific Gravity:.....	1.04
Solids:.....	22%
pH:.....	8.5
James Static Coefficient of Friction:...	0.6
Leveling:.....	Excellent
Film Formation:.....	Excellent
Gloss:.....	Excellent
Water resistance:.....	Excellent
Detergent resistance:.....	Excellent
Removability:.....	Excellent
Black heal mark resistance:.....	Excellent
Odor:.....	Mild acrylic
Appearance:.....	White emulsion

Manufactured by:
ABC COMPOUNDING COMPANY, INC.
ATLANTA, GA / DALLAS, TX

LX0104/1311



FEATURES

- Modified Acrylic Polymers
- Unsurpassed Leveling
- Excellent Burnish Response With No Powdering Or Dusting

BENEFITS

- Labor Saver Through Less Frequent Need To Buff, Burnish & Re-coat, And A Reduction In The Number Of Strippings

WHERE TO SELL

- Hospitals / Healthcare
- School Systems
- Grocery / Convenience Stores
- Shopping Centers / Malls
- Sports Facilities
- Office Buildings
- Airports

www.lynxclean.com

Lynx is a Registered Trademark of
ABC Compounding Co., Inc.